

ARMAFLEX SHEET

AL / KY / AL-KY



It is an elastomeric rubber based insulation material in the form of sheet with closed cell structure. It is manufactured to be used for air conditioning, heating and cooling systems. It can be faced with aluminium foil and can be self-adhesive.

Application

It is used on the exterior surfaces of the ducts and large diameter pipe lines in the heating, cooling and air conditioning systems for thermal insulation and condensation control purposes. For the spaces where there is heat transfer by radiation, using products faced with aluminium foil is recommended. The sheets are adhered to the duct surface by using a special adhesive that İzocam suggested. Joints should be tightly sealed and they should be covered with insulation tape afterwards if necessary. Taping should not result in thickness loss. For the application of self adhesive sheets there is no need to use any adhesive. The application should be protected against disruption and rupture. For the applications exposed to the sun, definitely a protective coat or a protective paint should be used. For indoor spaces getting natural sun, the products faced with aluminium foil can be used without requiring any coating against UV affect. For the outdoor applications, the surface should be coated within 5 days.

Thickness (mm)	Width x Length (mm)	Package (m ²)
6	1000 x 36000	36
9	1000 x 24000	24
13	1000 x 18000	18
19	1000 x 12000	12
25	1000 x 9000	9
32	1000 x 7000	7
40	1000 x 6000	6
50	1000 x 5000	5



- High thermal insulation
- High condensation control
- CFC free
- Environment friendly
- Highly flexible



TECHNICAL DATA SHEET

İzocam Armaflex Sheet

Properties	Symbol	Unit	Description						Tolerance	Standard	
Material	-	-	Elastomeric Rubber Foam						-	TS EN 14303	
Material Type	-	-	Armaflex Board	Armaflex AL	Armaflex KY	Armaflex AL-KY			-	-	
Facing	-	-	Unfaced	Al-foil (18 μ , reinforced, non-combustable)	Self adhesive film.	Al-foil, Self adhesive film.			-	-	
Reaction to fire **	-	-	B-s ₃ , d ₀	C-s ₃ , d ₀					-	TS EN 13501-1	
Max. Service Temperature	-	°C	-50 / 105			-50 / 85			-	-	
Length	L	mm	3000 ≤ L ≤ 60000						± 1,5 %	EN 822	
Width	w	mm	500 ≤ w ≤ 1200 *						± 2 %	EN 822	
Thickness	t	mm	6 ≤ t ≤ 50						t ≤ 6	±1,0	EN 823
									6 < t ≤ 19	±1,5	
									t > 19	±2,0	
Declared Thermal Conductivity	T _m	°C	-20	0	20	40	60	80	-	TS EN 12667 TS EN 12939	
	λ	W/m.K	0,034	0,036	0,038	0,040	0,043	0,045			
Water Vapor Diffusion Resistance Factor	μ	-	≥ 7000						-	EN 12086	
UV Resistance	-	-	Good						-	-	
Resistance to Oils	-	-	Good						-	-	
Resistance to Weather Conditions	-	-	Good						-	-	
Flexibility	-	-	Excellent						-	-	
Fungal Growth	-	-	None						-	-	
Packaging Material	-	-	Carton Box						-	-	
Other Information	İzocam Armaflex composed of more than 95 % closed cells. It is appropriate to DIN 1988/7 relating to corrosion. Product contains less than 0,2 % ammonium and less than 0,05 % chlorine ion that dissolved in water.										

* Standard width is 1000 mm.

** Sheets which are thicker than 32 mm classified as C-s₃, d₀

Safety Reminders for Loading, Unloading, Shipping and Storing

- These operations should be done indoors in case of rainy weather conditions.
- Loading and unloading should be done by (at least) two people.
- The products should be wrapped by a waterproof cover during shipping.
- Boxes should be carried by their handles.
- When the boxes piled in the truck body are being tied up hard padding (wood, cardboard, etc.) should be put on the corners of the packages to protect them against possible damages by ropes.
- The corners should be aligned when the boxes are superposed.
- Only backshutter of the truck body should be opened during unloading.
- Storing should be done indoors and the boxes should be put over flat floor.
- Maximum 6 boxes of the sheets with 6, 9, 13, 19, 25 and 32 mm thickness should be superposed. Maximum 3 boxes of the sheets with 40 and 50mm thickness should be superposed.
- Boxes should not be put into upright position.
- Boxes should not be stepped on and should not be used as steps.
- Products should not be unloaded by pushing or throwing from the truck.
- The truck should not be moved without wrapping and binding the boxes.
- The products should not be exposed to sun.
- Storage area should not be wet.

İzocam is not responsible for any problem because of misprinting. İzocam, the manufacturer, reserves the right to alter product specifications without prior notice. İzocam also manufactures special products upon request. For your requirements, you are requested to contact our Export Department.



NH / ARMAFLEX



It is a black coloured elastomeric rubber based insulation material in the form of sheet and pipe with closed cell structure which doesn't contain CFC halogen materials (chlorine, bromine, etc.) and PVC.

Application

It is used on the exterior surfaces of the ducts and large diameter pipe lines in the heating, cooling and air conditioning systems for thermal insulation and condensation control purposes. It is developed to use at battleships, merchant ships, transportation systems; in areas where there are crowds of people such as business and entertainment places, hospitals, airports in order to reduce the emissions of smoke and poisonous gases. The sheets are adhered to the duct surface by using a special adhesive that İzocam suggested. For the pipe applications, the pipe to be insulated and the rubber surface should fit properly and no gap should be left in between. Joints should be tightly sealed and they should be covered with insulation tape afterwards if necessary. Taping should not result in thickness loss. The application should be protected against disruption and rupture.

Board Dimensions		Thickness					
Width (mm)	Length (mm)	6 mm	10 mm	13 mm	19 mm	25 mm	32 mm
1000	15000	+					
1000	10000		+				
1000	8000			+			
1000	6000				+		
1000	4000					+	
1000	3000						+

Pipe Inner Diameter (mm)	Thickness			
	9 mm	13 mm	19 mm	25 mm
10	+	+	+	
12	+	+	+	
15	+	+	+	+
18	+	+	+	+
22	+	+	+	+
28	+	+	+	+
35	+	+	+	+
42	+	+	+	+
48	+	+	+	+
54	+	+	+	+
60	+	+	+	+
76	+	+	+	+
89	+	+	+	+



- Thermal insulation
- Condensation control
- Fire safety
- Environment friendly
- Highly flexible
- CFC free



TECHNICAL DATA SHEET

izocam NH / Armaflex

Properties	Symbol	Unit	Description			Tolerance	Standard
Material	-	-	Closed Cell Synthetic Rubber			-	-
Material Type	-	-	NH Sheet	NH Pipe			
Length	L	mm	$1500 \leq L \leq 3000$	2000		$\pm 1,5 \%$	-
Width	w	mm	1000			$\pm 2 \%$	-
Inner Diameter	D_n	mm		$10 \leq D_n \leq 89$		$\Theta +1 \leq \Theta \leq \Theta +4$	-
Thickness	t	mm	$6 \leq t \leq 32$	$9 \leq t \leq 25$	$t \leq 6$	$t \leq 8$	$\pm 1,0$
					$6 < t \leq 19$	$8 < t \leq 18$	$\pm 1,5$
					$t > 19$	$t \geq 19$	$\pm 2,0$
Reaction to fire	-	-	B-s ₃ , d ₀			-	EN 13501-1
Declared Thermal Conductivity	T_m	°C	0	24	40	-	ASTMC 177
	λ	W/m.K	0,036	0,039	0,041		
Max. Service Temperature	-	°C	-50 / 105			-	DIN EN 14706 DIN EN 14707 DIN EN 14303
Water Vapor Diffusion Resistance Factor	μ	-	≥ 2000			-	DIN 52615 EN 12086 EN 13469
UV Resistance	-	-	Excellent			-	-
Resistance to Oils	-	-	Good			-	-
Resistance to Weather Conditions	-	-	Good			-	-
Flexibility	-	-	Excellent			-	-
Fungal Growth	-	-	None			-	-
Packaging Material	-	-	Carton Box			-	-
Other Information	NH/Armaflex is a nitrile rubber foam that does not consist of chlorine and bromide ions.						

Safety Reminders for Loading, Unloading, Shipping and Storing

- These operations should be done indoors in case of rainy weather conditions.
- Loading and unloading should be done by (at least) two people.
- The products should be wrapped by a waterproof cover during shipping.
- Boxes should be carried by their handles
- When the boxes piled in the truck body are being tied up hard padding (wood, cardboard, etc.) should be put on the corners of the packages to protect them against possible damages by ropes.
- The corners should be aligned when the boxes are superposed.
- Only backshutter of the truck body should be opened during unloading.
- Storing should be done indoors and the boxes should be put over flat floor.
- Maximum 5 boxes should be superposed.
- Boxes should not be put into upright position.
- Boxes should not be stepped on and should not be used as steps.
- Products should not be unloaded by pushing or throwing from the truck.
- The truck should not be moved without wrapping and binding the boxes.
- The products should not be exposed to sun.
- Storage area should not be wet.

Izocam is not responsible for any problem because of misprinting. Izocam, the manufacturer, reserves the right to alter product specifications without prior notice. Izocam also manufactures special products upon request. For your requirements, you are requested to contact our Export Department.



ENAFNH2013/01





It is an elastomeric rubber based insulation material in the form of sheet and pipe with closed cell structure. It is manufactured to be used for thermal insulation and condensation control purposes. It has high thermal insulation value.

Application

It is used on the exterior surfaces of the ducts and large diameter pipe lines in the heating, cooling and air conditioning systems for thermal insulation and condensation control purposes. Armaflex HT products can be used at temperatures up to 175 °C. The sheets are adhered to the duct surface by using a special adhesive that İzocam suggested. For the pipe applications, the pipe to be insulated and the rubber surface should fit properly and no gap should be left in between. Joints should be tightly sealed and they should be covered with insulation tape afterwards if necessary. Taping should not result in thickness loss. The application should be protected against disruption and rupture. Since it is resistant to sun and UV rays, it can be used securely at solar energy collector systems located outdoors, hot gas and vapour lines, etc. without requiring any protective paint.

Board Dimensions		Thickness			
Width (mm)	Length (mm)	10 mm	13 mm	19 mm	25 mm
1000	10000	+			
1000	8000		+		
1000	6000			+	
1000	4000				+

Pipe Inner Diameter (mm) *	Thickness			
	10 mm	13 mm	19 mm	25 mm
10	+	+		
12	+	+	+	+
15	+	+	+	+
18	+	+	+	+
22	+	+	+	+
28	+	+	+	+
35	+	+	+	+
42	+	+	+	+
48	+	+	+	+
54	+	+	+	+
60	+	+	+	+
76	+	+	+	+
89	+	+	+	+

* Pipe length is 2000 mm.



- Condensation control
- Thermal insulation
- Environment friendly
- CFC free
- Highly flexible

TECHNICAL DATA SHEET

Izocam HT / Armaflex

Properties	Symbol	Unit	Description		Tolerance	Standard	
Material	-	-	Closed Cell Synthetic Rubber		-	-	
Material Type	-	-	HT Sheet	HT Pipe			
Length	L	m	$4 \leq L \leq 10$	2	$\pm 1,5 \%$	-	
Width	w	mm	1000		$\pm 2 \%$	-	
Inner Diameter	D_n	mm		$10 \leq D_n \leq 89$	$\Theta +1 \leq \Theta \leq \Theta +4$	-	
Thickness	t	mm	$10 \leq t \leq 25$	$10 \leq t \leq 25$	$t \leq 6$	$t \leq 8$	$\pm 1,0$
					$6 < t \leq 19$	$8 < t \leq 18$	$\pm 1,5$
					$t > 19$	$t \geq 19$	$\pm 2,0$
Facing	-	-	-		-	-	
Reaction to fire	-	-	B-s ₃ , d ₀		-	EN 13501-1	
Declared Thermal Conductivity (0 °C)	λ_D	W/m.K	< 0,040		-	DIN 52613	
Max. Service Temperature	-	°C	-50 / 175		-	-	
Water Vapor Diffusion Resistance Factor	μ	-	≥ 3000		-	DIN 52615	
UV Resistance	-	-	Excellent		-	-	
Resistance to Oils	-	-	Good		-	-	
Resistance to Weather Conditions	-	-	Good		-	-	
Flexibility	-	-	Excellent		-	-	
Fungal Growth	-	-	None		-	-	
Packaging Material	-	-	Carton Box		-	-	
Other Information	HT/Armaflex is a nitrile rubber foam that does not consist of chlorine and bromide ions.						

Safety Reminders for Loading, Unloading, Shipping and Storing

- These operations should be done indoors in case of rainy weather conditions.
- Loading and unloading should be done by (at least) two people.
- The products should be wrapped by a waterproof cover during shipping.
- Boxes should be carried by their handles.
- When the boxes piled in the truck body are being tied up hard padding (wood, cardboard, etc.) should be put on the corners of the packages to protect them against possible damages by ropes.
- The corners should be aligned when the boxes are superposed.
- Only backshutter of the truck body should be opened during unloading.
- Storing should be done indoors and the boxes should be put over flat floor.
- Maximum 5 boxes should be superposed.
- Boxes should not be put into upright position.
- Boxes should not be stepped on and should not be used as steps.
- Products should not be unloaded by pushing or throwing from the truck.
- The truck should not be moved without wrapping and binding the boxes.
- The products should not be exposed to sun.
- Storage area should not be wet.

Izocam is not responsible for any problem because of misprinting. Izocam, the manufacturer, reserves the right to alter product specifications without prior notice. Izocam also manufactures special products upon request. For your requirements, you are requested to contact our Export Department.





ARMAFLEX PIPE



It is an elastomeric rubber based insulation material in the form of pipe with closed cell structure. It is manufactured to be used for air conditioning, heating and cooling systems.

Application

It is used at the exterior surfaces of the ducts in the heating, cooling, ventilating and air conditioning systems for thermal insulation and condensation control purposes. The pipe to be insulated and the rubber surface should fit properly and no gap should be left in between. Joints should be tightly sealed. The application should be protected against disruption and rupture. For the applications exposed to sun, a protective coat or a protective paint should be used against UV affect. For the outdoor applications, the surface should be coated within 5 days.

Inner Diameter	Copper Pipe	Steel Pipe	Package						
			6	9	13	19	25	32	
mm	inch	inch	mm	mm	mm	mm	mm	mm	
6	1/4"		608	356	210				
8	5/16"		504	308	190				
10	3/8"	1/8"	408	260	168	96			
12	1/2"		350	230	156	92			
15	5/8"	1/4"	282	194	132	80			
18	3/4"	3/8"	232	166	116	72	50	32	
20			214						
22	7/8"	1/2"	186	136	96	62	42	32	
25	1"		160	120	86	56	40	28	
28	1 1/8"	3/4"	136	104	78	52	40	24	
35	1 3/8"	1"	98	80	60	42	24	22	
42	1 5/8"	1 1/4"	86	64	50	36	22	16	
48		1 1/2"		52	42	32	18	16	
54	2 1/8"			44	36	28	16	14	
60	2 3/8"	2"		38	32	24	16	14	
64	2 1/2"			38	28	24	14	12	
70	2 5/8"			30	28	20	14	12	
76	3"	2 1/2"		26	22	18	14	12	
80	3 1/8"			24	20	16	12	10	
89	3 1/2"	3"		20	18	14	12	10	
102		3 1/2"		16	12	12	10	8	
108	4 1/4"			16	12	12	10	8	
114	4 1/2"	4"		16	12	10	10	8	
140		5"			8	10	8	4	
160	6 1/4"				6	8	6	2	



- High thermal insulation
- High condensation control
- CFC free
- Environment friendly
- Highly flexible



TECHNICAL DATA SHEET

İzocam Armaflex Pipe

Properties	Symbol	Unit	Description						Tolerance	Standard	
Material	-	-	Closed Cell Synthetic Rubber						-	TS EN 14304	
Length	L	m	$2 \leq L \leq 50$ *						$\pm 1,5$ %	TS EN 13467	
Inner Diameter	D_n	mm	$6 \leq D_n \leq 100$						$\Theta+1 \leq \Theta \leq \Theta+4$	TS EN 13467	
			$D_n > 100$						$\Theta+1 \leq \Theta \leq \Theta+6$		
Thickness	t	mm	$6 \leq t \leq 32$						$t \leq 8$	$\pm 1,0$	TS EN 13467
									$8 < t \leq 18$	$\pm 1,5$	
									$18 < t \leq 31$	$\pm 2,5$	
									$t \geq 32$	$\pm 3,0$	
Reaction to fire	-	-	B-s ₂ , d ₀						-	TS EN 13501-1	
Declared Thermal Conductivity	T_m	°C	-20	0	20	40	60	80	-	EN 12667 EN ISO 8497	
	λ	W/m.K	0,034	0,036	0,038	0,040	0,043	0,045			
Max. Service Temperature	-	°C	-50 / 105						-	-	
Water Vapor Diffusion Resistance Factor	μ	-	≥ 7000						-	EN 13469	
UV Resistance	-	-	Good						-	-	
Resistance to Oils	-	-	Good						-	-	
Resistance to Weather Conditions	-	-	Good						-	-	
Flexibility	-	-	Excellent						-	-	
Fungal Growth	-	-	None						-	-	
Packaging Material	-	-	Carton Box						-	-	
Other Information	İzocam Armaflex composed of more than 95 % closed cells. It is appropriate to DIN 1988/7 relating to corrosion. Product contains less than 0,2 % ammonium and less than 0,05 % chlorine ion that dissolved in water.										

* Standard length is 2000 mm.

Safety Reminders for Loading, Unloading, Shipping and Storing

- These operations should be done indoors in case of rainy weather conditions.
- Loading and unloading should be done by (at least) two people.
- The products should be wrapped by a waterproof cover during shipping.
- Boxes should be carried by their handles.
- When the boxes piled in the truck body are being tied up hard padding (wood, cardboard, etc.) should be put on the corners of the packages to protect them against possible damages by ropes.
- The corners should be aligned when the boxes are superposed.
- Only backshutter of the truck body should be opened during unloading.
- Storing should be done indoors and the boxes should be put over flat floor.
- Maximum 5 boxes should be superposed.
- Boxes should not be put into upright position.
- Boxes should not be stepped on and should not be used as steps.
- Products should not be unloaded by pushing or throwing from the truck.
- The truck should not be moved without wrapping and binding the packages.
- The products should not be exposed to sun.
- Storage area should not be wet.

İzocam is not responsible for any problem because of misprinting. İzocam, the manufacturer, reserves the right to alter product specifications without prior notice. İzocam also manufactures special products upon request. For your requirements, you are requested to contact our Export Department.



ENAFB2013/01



ARMAFLEX - S



It is an elastomeric rubber based insulation material in the form of pipe with closed cell structure. It is manufactured to be used for heating and cooling systems.

Application

It is used at the exterior surfaces of the ducts in the heating, cooling, ventilating and air conditioning systems for thermal insulation and condensation control purposes. The pipe to be insulated and the rubber surface should fit properly and no gap should be left in between. Joints should be tightly sealed. The application should be protected against disruption and rupture. For the applications exposed to sun, a protective coat or a protective paint should be used against UV affect. For the outdoor applications, the surface should be coated within 5 days.

Inner Diameter	Copper Pipe	Steel Pipe	Package			
			Thickness			
mm	inch	inch	6 mm	9 mm	13 mm	19 mm
6	1/4"		608	356	210	
8	5/16"		504	308	190	
10	3/8"	1/8"	408	260	168	96
12	1/2"		350	230	156	92
15	5/8"	1/4"	282	194	132	80
18	3/4"	3/8"	232	166	116	72
20			214			
22	7/8"	1/2"	186	136	96	62
25	1"		160	120	86	56
28	1 1/8"	3/4"	136	104	78	52
35	1 3/8"	1"	98	80	60	42
42	1 5/8"	1 1/4"	86	64	50	36
48		1 1/2"		52	42	32
54	2 1/8"			44	36	28
60	2 3/8"	2"		38	32	24
64	2 1/2"			38	28	24
70	2 5/8"			30	28	20
76	3"	2 1/2"		26	22	18
80	3 1/8"			24	20	16
89	3 1/2"	3"		20	18	14
102		3 1/2"		16	12	12
108	4 1/4"			16	12	12
114	4 1/2"	4"		16	12	10



- Thermal insulation
- Condensation control
- CFC free
- Environment friendly
- Highly flexible



TECHNICAL DATA SHEET

izocam Armaflex - S

Properties	Symbol	Unit	Description						Tolerance	Standard	
Material	-	-	Closed Cell Synthetic Rubber						-	TS EN 14304	
Length	L	m	$2 \leq L \leq 50$ *						$\pm 1,5$ %	TS EN 13467	
Inner Diameter	D_n	mm	$6 \leq D_n \leq 100$						$\Theta+1 \leq \Theta \leq \Theta+4$	TS EN 13467	
			$D_n > 100$						$\Theta+1 \leq \Theta \leq \Theta+6$		
Thickness	t	mm	$6 \leq t \leq 19$						t \leq 8	$\pm 1,0$	TS EN 13467
									8<t \leq 18	$\pm 1,5$	
									t \geq 19	$\pm 2,5$	
Reaction to fire	-	-	B-s ₂ , d ₀						-	TS EN 13501-1	
Declared Thermal Conductivity	T _m	°C	-20	0	20	40	60	80	-	EN 12667 EN ISO 8497	
	λ	W/m.K	0,034	0,036	0,038	0,040	0,043	0,045			
Max. Service Temperature	-	°C	-50 / 105						-	-	
Water Vapor Diffusion Resistance Factor	μ	-	≥ 3000						-	DIN 52615	
UV Resistance	-	-	Good						-	-	
Resistance to Oils	-	-	Good						-	-	
Resistance to Weather Conditions	-	-	Good						-	-	
Flexibility	-	-	Excellent						-	-	
Fungal Growth	-	-	None						-	-	
Packaging Material	-	-	Carton Box						-	-	
Other Information	Izocam Armaflex-S composed of more than 95 % closed cells. It is appropriate to DIN 1988/7 relating to corrosion. Product contains less than 0,2 % ammonium and less than 0,05 % chlorine ion that dissolved in water.										

* Standard length is 2000 mm.

Safety Reminders for Loading, Unloading, Shipping and Storing

- These operations should be done indoors in case of rainy weather conditions.
- Loading and unloading should be done by (at least) two people.
- The products should be wrapped by a waterproof cover during shipping.
- Boxes should be carried by their handles.
- When the boxes piled in the truck body are being tied up hard padding (wood, cardboard, etc.) should be put on the corners of the packages to protect them against possible damages by ropes.
- The corners should be aligned when the boxes are superposed.
- Only backshutter of the truck body should be opened during unloading.
- Storing should be done indoors and the boxes should be put over flat floor.
- Maximum 5 boxes should be superposed.
- Boxes should not be put into upright position.
- Boxes should not be stepped on and should not be used as steps.
- Products should not be unloaded by pushing or throwing from the truck.
- The truck should not be moved without wrapping and binding the packages.
- The products should not be exposed to sun.
- Storage area should not be wet.



Izocam is not responsible for any problem because of misprinting. Izocam, the manufacturer, reserves the right to alter product specifications without prior notice. Izocam also manufactures special products upon request. For your requirements, you are requested to contact our Export Department.



ARMAFLEX - SPLIT



It is an elastomeric rubber based insulation material in the form of pipe with closed cell structure. It is manufactured to be used for cooling and split systems.

Application

It is used in split cooling systems for thermal insulation and condensation control purposes. The pipe to be insulated and the rubber surface should fit properly and no gap should be left in between. Joints should be tightly sealed. The application should be protected against disruption and rupture. İzocam Armaflex-Split is put into the box without to be cut as one piece. The material is pulled out of the box opening and cut to desired size. By that way, the box is preserved until the next time. For the applications exposed to sun, a protective coat or a protective paint should be used against UV affect. For the outdoor applications, the surface should be coated within 5 days.

Inner Diameter (mm)	Copper Pipe Outer Diameter (inch)	Steel Pipe Outer Diameter (inch)	Package (m/box)
6	1/4"	-	50
8	5/16"	-	50
10	3/8"	1/8"	50
12	1/2"	-	50
15	5/8"	1/4"	50
18	3/4"	3/8"	40
22	7/8"	1/2"	30
28	1 1/8"	3/4"	25



- Thermal insulation
- Condensation control
- CFC free
- Environment friendly
- Highly flexible



TECHNICAL DATA SHEET

Izocam Armaflex - Split

Properties	Symbol	Unit	Description						Tolerance	Standard
Material	-	-	Closed Cell Synthetic Rubber						-	TS EN 14304
Length	L	m	25 ≤ L ≤ 50						± 1,5 %	TS EN 13467
Inner Diameter	D _n	mm	6 ≤ D _n ≤ 28						D _n +1 ≤ D _n ≤ D _n +4	TS EN 13467
Thickness	t	mm	6						±1,0	TS EN 13467
Reaction to fire	-	-	B-s ₂ , d ₀						-	TS EN 13501-1
Declared Thermal Conductivity	T _m	°C	-20	0	20	40	60	80	-	TS EN 12667 EN ISO 8497
	λ	W/m.K	0,034	0,036	0,038	0,040	0,043	0,045		
Max. Service Temperature	-	°C	-50 / 105						-	-
Water Vapor Diffusion Resistance Factor	μ	-	≥ 3000						-	EN 13469
UV Resistance	-	-	Good						-	-
Resistance to Oils	-	-	Good						-	-
Resistance to Weather Conditions	-	-	Good						-	-
Flexibility	-	-	Excellent						-	-
Fungal Growth	-	-	None						-	-
Packaging Material	-	-	Carton Box						-	-
Other Information	Izocam Armaflex Split composed of more than 95 % closed cells. It is appropriate to DIN 1988/7 relating to corrosion. Product contains less than 0,2 % ammonium and less than 0,05 % chlorine ion that dissolved in water.									

Safety Reminders for Loading, Unloading, Shipping and Storing

- These operations should be done indoors in case of rainy weather conditions.
- Loading and unloading should be done by (at least) two people.
- The products should be wrapped by a waterproof cover during shipping.
- Boxes should be carried by their handles.
- When the boxes piled in the truck body are being tied up hard padding (wood, cardboard, etc.) should be put on the corners of the packages to protect them against possible damages by ropes.
- The corners should be aligned when the boxes are superposed.
- Only backshutter of the truck body should be opened during unloading.
- Storing should be done indoors and the boxes should be put over flat floor.
- Maximum 5 boxes should be superposed.
- Boxes should not be put into upright position.
- Boxes should not be stepped on and should not be used as steps.
- Products should not be unloaded by pushing or throwing from the truck.
- The truck should not be moved without wrapping and binding the packages.
- The products should not be exposed to sun.
- Storage area should not be wet.



Izocam is not responsible for any problem because of misprinting. Izocam, the manufacturer, reserves the right to alter product specifications without prior notice. Izocam also manufactures special products upon request. For your requirements, you are requested to contact our Export Department.

